

Material: ZX-100K

EN 1.0

Properties	Symbol Unit	Standard	Value
Information			
Material code	-	-	Internal Standard
Colour	-	-	White
Density	ρ	kg/dm³	ISO 1183 1,35
Mechanical			
Compressive modulus	E_c	MPa	DIN EN ISO 604 3150
Elastic limit	σ_{el}	MPa	Internal Standard 75
Compressive stress at yield	σ_y	MPa	DIN EN ISO 604 n.v.
Compressive strength	σ_M	MPa	DIN EN ISO 604 n.v.
Compressive stress at 3,5% strain	$\sigma_{3,5\%}$	MPa	DIN EN ISO 604 30
Compressive strength (0,01 h)	σ_M	MPa	Internal Standard 75
Compressive strength (100 h)	σ_M	MPa	Internal Standard 60
Compressive strength (10000 h)	σ_M	MPa	Internal Standard 30
Compressive stress at break	σ_B	MPa	DIN EN ISO 604 k.Br.
Elastic compression limit	ε_{el}	%	Internal Standard 6
Nominal compressive yield strain	ε_{cy}	%	DIN EN ISO 604 n.v.
Nominal compressive strain at compressive strength	ε_{cM}	%	DIN EN ISO 604 n.v.
Nominal compressive strain at break	ε_{cB}	%	DIN EN ISO 604 k.Br.
Modulus in tension (tensile modulus)	E_t	MPa	DIN EN ISO 527 2900
Elastic limit	σ_{el}	MPa	Internal Standard 65
Tensile stress at yield	σ_y	MPa	DIN EN ISO 527 78
Tensile strength	σ_M	MPa	DIN EN ISO 527 78
Tensile stress at break	σ_B	MPa	DIN EN ISO 527 70
Elastic yield point	ε_{el}	%	Internal Standard 1,6
Yield strain	ε_y	%	DIN EN ISO 527 6
Elongation at maximum force	ε_M	%	DIN EN ISO 527 6
Tensile elongation at break	ε_B	%	DIN EN ISO 527 9,5
Modulus in flexure	E_f	MPa	DIN EN ISO 178 3300
Outer fibre stress at 3,5% outer fibre strain	$\sigma_{f3,5}$	MPa	DIN EN ISO 178 96
Flexural strength	σ_{fM}	MPa	DIN EN ISO 178 117
Flexural stress at break	σ_{fB}	MPa	DIN EN ISO 178 k.Br.
Elongation at flexural yield stress	ε_M	%	DIN EN ISO 178 6,1
Flexural elongation at break	ε_B	%	DIN EN ISO 178 k.Br.
Creep modulus at 1% deformation after 1000h	E	N/mm²	DIN 53444 2000
Stress at 1% deformation after 1000h	$\sigma_{1\%}$	N/mm²	DIN 53444 22
Creep resistance	-	-	Relative value ③
Ball indentation hardness H358/30 (H132/30) [H49/30]	HB	N/mm²	DIN 2039 136
Shore A hardness	-	Shore	DIN 53505 >100
Shore D hardness	-	Shore	DIN 53505 84
Impact strength Charpy notched	-	kJ/m²	EN ISO 179/1eU 54
Impact strength Charpy notched	-	kJ/m²	EN ISO 179/1eA 6,0
Loss tangent (1Hz)	$\tan\delta$	1	Internal Standard 0,077
Fatigue strength at 20°C, 106 stress cycles, 1 Hz	-	MPa	Internal Standard 52
Thermal			
Continuous operating temperature (long term)	RTi	°C	UL 746B 110
Short term operating temperature (3 h)	-	°C	Internal Standard 140
Maximum RTi temperature for bushings when pressed	-	°C	Internal Standard 65
Melting temperature	T_m	°C	DSC 250
Glass transition temperature	T_g	°C	DSC 78
Coefficient of thermal expansion up to 100°C	α	10⁻⁵/K	ISO E 830 8
Coefficient of thermal expansion up to 150°C	α	10⁻⁵/K	ISO E 831 12
Heat distortion temperature HDT/A 1,8 MPa	HDT(A)	°C	DIN EN ISO 75 75
Thermal conductivity	λ	W/(m*K)	DIN 52612 0,24
Specific heat capacity	c_p	kJ/(kg*K)	DSC 1,06
Fire behaviour (3,2mm) UL94	-	-	UL 94 HB 94HB
Limiting oxygen index (LOI)	%	LOI	DIN EN ISO 4589 24

Properties	Symbol Unit	Standard	Value
Electrical			
Volume resistivity	R_D	Ω*cm	IEC 60093 2E14
Surface resistance	R_O	Ω	IEC 60093 6E10
Penetration resistance	E	kV/mm	IEC 243 21,5
Tracking resistance	-	V	IEC 112 305
Dielectric constant (110Hz)	-	1	IEC 250 3,4
Dissipation factor (110Hz)	$\tan\delta$	1	IEC 112 0,015
PV values			
Max. surface pressure v=1m/min	p_{zul}	N/mm²	35
Max. surface pressure v=10m/min	p_{zul}	N/mm²	2,59
Max. surface pressure v=100m/min	p_{zul}	N/mm²	0,08
Max. surface pressure v=200m/min	p_{zul}	N/mm²	0,04
Evolution of heat with v=1m/min	-	°C	Internal test radial bushing 42
Evolution of heat with v=10m/min	-	°C	60
Evolution of heat with v=100m/min	-	°C	35
Evolution of heat with v=200m/min	-	°C	64
Friction			
μ static 20°C dry operation	$\mu_{stat.}$	1	Internal Standard 0,11
μ dynamic 20°C dry operation	$\mu_{dyn.}$	1	Inclined plane 0,08
μ dynamic 100°C dry operation	$\mu_{dyn.}$	1	0,15
Wear			
Wear factor at 20°C	-	mm/100km	Internal test 0,07
Wear factor at 100°C	-	mm/100km	periodic transla- tive movement 0,21
Wear factor at 200°C	-	mm/100km	n.d. n.d.
Wear factor at 240°C	-	mm/100km	n.d.
Available as			
Tubes (hollow rods) up to ø (de)	-	-	- ✓
Sheets up to max. thickness	-	-	- ✓
Rods up to ø (de)	-	-	- ✓
Plastic granules	-	-	- (✓)
Injection moulded parts	-	-	- (✓)
Machined parts	-	-	- ✓
Precision			
Dimensional stability with moisture absorption	-	-	Relative value ⑦
Water absorption 23°C / RMC 93%	-	%	DIN EN ISO 62 0,3
Water absorption until an equilibrium moisture content	-	%	DIN EN ISO 62 0,5
Dimensional stability with temperature variation	-	-	Relative value ③
High precision bushings (negative clearance)	-	-	- ✓
Alignment adjustment	-	-	Relative value ⑤
Environmental influences			
Suitable for use in water	-	-	- ✓
Resistance against hot water	-	°C	- 80
Resistance against dust, dirt, abrasive substances	-	-	Relative value ⑥
UV rays resistance	-	-	Relative value ⑨
Suitable for outdoor use	-	-	Relative value ⑧
Resistance to chemicals	-	-	Relative value ⑦
FDA compliant	-	-	- ✓
Suitable for vacuum	-	-	- ✓
Rate of desorption	a_{1h}	mbar¹l/(s/cm²)	- 1,83 E-6 α=0,44
ROHS / WEEE	-	-	- ✓
Free from silicone	-	-	- ✓
Free from PTFE	-	-	- ✓
Sterilization			
Resistant against disinfectant	-	-	- ✓
Moist heat sterilization	-	-	Relative value ⑥
Gamma-rays radiation sterilization	-	-	Relative value ③
Chemical sterilization	-	-	Relative value ⑦
UV-sterilization	-	-	Relative value ⑦



Legal Information

All the tests are been made with a standard conditioning atmosphere of 23°C (at the moment no other temperature is available). The specified values are established from average values of several tests and they correspond to our today's knowledge. They are only to be used as information about our products and as help for the material selection. With these values, we do not ensure specific properties, or the suitability for certain application, therefore we do not assume any legal responsibility for an improper usage. The used test pieces have been machined from extruded semi-finished material. Since the plastics' properties depend on the manufacturing process (extrusion, injection moulding), on the dimensions of the semi finished material and on the degree of crystallinity, the actual properties of a specific product may slightly deviate from the tested ones. For information about divergent properties do not hesitate to contact us. On request we advise you regarding the most appropriate component design and the definition of material specifications more suitable to your application data. Notwithstanding, the customer bears all the responsibility for the thorough examination of suitability, efficiency, efficacy and safety of the chosen products in pharmaceutical applications, medical devices or other end uses.

Legend

- ① Low
- ⑩ High
- ✓ Applicable
- ✗ Not applicable
- (✓) Limited
- k.Br. No break
- n.d. Not feasible
- Not determined
- n.v. Non-existent